



S 6 ISO + V6
(a richiesta / on request / auf Anfrage)
D1 < 38 con / with / mit 3
D1 ≥ 38 con / with / mit 4

CEA

COLONNA ESTRAIBILE
DEMOUNTABLE GUIDE PILLAR
FÜHRUNGSSÄULE MIT BUND

Material: 1.7131 - Hardness: 61-63 HRC

| Code | D1 | Code | D1 | L1 | L2 | D3 | M | R |
|----------|----|----------|----|-----|----|----|----|------|
| CEA19100 | 19 | CEA20100 | 20 | 100 | 23 | 25 | M8 | 18 |
| CEA19112 | | CEA20112 | | 112 | | | | |
| CEA19125 | | CEA20125 | | 125 | | | | |
| CEA19140 | | CEA20140 | | 140 | | | | |
| CEA19160 | | CEA20160 | | 160 | | | | |
| CEA19180 | | CEA20180 | | 180 | | | | |
| CEA19200 | | CEA20200 | | 200 | | | | |
| CEA24100 | 24 | CEA25100 | 25 | 100 | 30 | 32 | M8 | 21,5 |
| CEA24112 | | CEA25112 | | 112 | | | | |
| CEA24125 | | CEA25125 | | 125 | | | | |
| CEA24140 | | CEA25140 | | 140 | | | | |
| CEA24160 | | CEA25160 | | 160 | | | | |
| CEA24180 | | CEA25180 | | 180 | | | | |
| CEA24200 | | CEA25200 | | 200 | | | | |
| CEA24224 | | CEA25224 | | 224 | | | | |
| CEA24250 | | CEA25250 | | 250 | | | | |
| CEA30112 | 30 | CEA32112 | 32 | 112 | 37 | 40 | M8 | 25,5 |
| CEA30125 | | CEA32125 | | 125 | | | | |
| CEA30140 | | CEA32140 | | 140 | | | | |
| CEA30160 | | CEA32160 | | 160 | | | | |
| CEA30180 | | CEA32180 | | 180 | | | | |
| CEA30200 | | CEA32200 | | 200 | | | | |
| CEA30224 | | CEA32224 | | 224 | | | | |
| CEA30250 | | CEA32250 | | 250 | | | | |
| CEA30280 | | CEA32280 | | 280 | | | | |
| CEA30315 | | CEA32315 | | 315 | | | | |
| CEA38125 | 38 | CEA40125 | 40 | 125 | 37 | 50 | M8 | 30,5 |
| CEA38140 | | CEA40140 | | 140 | | | | |
| CEA38160 | | CEA40160 | | 160 | | | | |
| CEA38180 | | CEA40180 | | 180 | | | | |
| CEA38200 | | CEA40200 | | 200 | | | | |
| CEA38224 | | CEA40224 | | 224 | | | | |
| CEA38250 | | CEA40250 | | 250 | | | | |
| CEA38280 | | CEA40280 | | 280 | | | | |
| CEA38315 | | CEA40315 | | 315 | | | | |
| CEA38355 | | CEA40355 | | 355 | | | | |

