

RT SERIES

RT 4200



Ordering-Example:

Special Sizes Available On Request.

K 32 R (Nissan)	E24.54.815.G (PSA)	EM24.54.700 (Renault)
SMS DNH 3203n Rev.3 (TOYOTA)		

OSAS + OSM = OVER STROKE ACTIVE SAFETY + OVER STROKE MARKER

ACTIVE SAFETY

The new code will be supplied only when the old will be out of stock

easu MANIFOLD

* F_{1i} = Isothermal end force at 100% Cu

** F_{1p} = Polytrophic end force at 100% Cu

	0 - 80 °C 32 - 176 °F	ΔP ± 0,33 %/°C	P max 150 bar 2175 psi	P min 20 bar 290 psi	S 28,27 cm ² 4.382 in ²	SPM ~ 20 - 100 (at 20°C)	Max Speed 1,8 m/s 70.8 in/s	Maintenance kit 39BMRV04200C
--	--------------------------	---------------------------	-------------------------------------	-----------------------------------	--	---------------------------------------	--	--

CODE PHASING OUT from 04/2021	NEW	Cu		L		L min		F0 Initial force		F1i End force *		F1p End force **		V0		PED 2014/68/EU		
		mm	inch	mm	inch	mm	inch	daN	lb	daN	lb	daN	lb	cm ³	in ³		~Kg	~lb
RT 4200 - 016 - A	♦RT 4200 - 016 - B	16	0.63	94	3.70	78	3.07			6103	13720	7197	16179	172	10.48	2,97	6.55	✓
RT 4200 - 019 - A	♦RT 4200 - 019 - B	19	0.75	100	3.94	81	3.19			6269	14093	7458	16767	192	11.71	3,05	6.72	✓
RT 4200 - 025 - A	♦RT 4200 - 025 - B	25	0.98	112	4.41	87	3.43			6531	14682	7874	17702	232	14.18	3,20	7.05	✓
RT 4200 - 032 - A	♦RT 4200 - 032 - B	32	1.26	126	4.96	94	3.70			6755	15186	8236	18515	280	17.06	3,37	7.43	✓
RT 4200 - 038 - A	RT 4200 - 038 - B	38	1.50	138	5.43	100	3.94	4240	9532	6902	15517	8475	19052	320	19.52	3,52	7.76	✓
RT 4200 - 050 - A	RT 4200 - 050 - B	50	1.97	162	6.38	112	4.41	± 5% 150 bar 2175 psi + 20 °C + 68 °F		7117	16001	8827	19844	401	24.45	3,82	8.42	✓
RT 4200 - 063 - A	RT 4200 - 063 - B	63	2.48	188	7.40	125	4.92			7278	16361	9092	20440	488	29.80	4,14	9.13	✓
RT 4200 - 075 - A	RT 4200 - 075 - B	75	2.95	212	8.35	137	5.39			7386	16604	9272	20843	569	34.73	4,44	9.79	✓
RT 4200 - 080 - A	RT 4200 - 080 - B	80	3.15	222	8.74	142	5.59			7423	16687	9333	20982	603	36.79	4,57	10.08	✓
RT 4200 - 100 - A	RT 4200 - 100 - B	100	3.94	262	10.31	162	6.38			7539	16949	9529	21421	738	45.01	5,07	11.18	✓
RT 4200 - 125 - A	RT 4200 - 125 - B	125	4.92	312	12.28	187	7.36			7639	17173	9696	21798	906	55.29	5,69	12.54	✓

♦ Disposable

