

S SERIES

S 750



Ordering-Example:

Special Sizes Available On Request.

B8 3180 220 000 003(MB)	EM24.54.700 (Renault)	SES-K 5404e (Suzuki)
-------------------------	-----------------------	----------------------

OSAS + OSM = OVER STROKE ACTIVE SAFETY + OVER STROKE MARKER

ACTIVE SAFETY

The new code will be supplied only when the old will be out of stock

easu MANIFOLD

* F_{1i} = Isothermal end force at 100% Cu

** F_{1p} = Polytrophic end force at 100% Cu

	0 - 80 °C 32 - 176 °F	ΔP ± 0.33 %/°C	P max 150 bar 2175 psi	P min 20 bar 290 psi	S 4.91 cm ² 0.761 in ²	SPM ~ 30 - 80 (at 20°C)	Max Speed 1.8 m/s 70.8 in/s	Maintenance kit 39BMS00750B
--	--------------------------	---------------------------	-------------------------------------	-----------------------------------	---	--------------------------------------	--	---------------------------------------

CODE PHASING OUT from 04/2021	NEW	Cu		L		L min		F0 Initial force		F1i End force *		F1p End force **		V0		PED 2014/68/EU			
		mm	inch	mm	inch	mm	inch	daN	lb	daN	lb	daN	lb	cm ³	in ³	~Kg	~lb	✓	
S 750 - 006 - B	◆ S 750 - 006 - C	6	0.24	62	2.44	56	2.20	± 5% 150 bar 2175 psi + 20 °C +68 °F	906	2038	1016	2283	18,4	1.12	0,60	1.32	✓		
S 750 - 013 - B	◆ S 750 - 013 - C	13	0.51	76	2.99	63	2.48		994	2234	1147	2579	28,7	1.75	0,66	1.46	✓		
S 750 - 019 - B	S 750 - 019 - C	19	0.75	88	3.46	69	2.72		1035	2326	1211	2722	37,5	2.29	0,71	1.57	✓		
S 750 - 025 - B	S 750 - 025 - C	25	0.98	100	3.94	75	2.95		1062	2387	1253	2818	46,3	2.83	0,75	1.65	✓		
S 750 - 038 - B	S 750 - 038 - C	38	1.50	126	4.96	88	3.46		740	1664	1098	2468	1309	2944	65,5	4.00	0,85	1.87	✓
S 750 - 050 - B	S 750 - 050 - C	50	1.97	150	5.91	100	3.94		1117	2511	1340	3012	83,1	5.07	0,95	2.09	✓		
S 750 - 063 - B	S 750 - 063 - C	63	2.48	176	6.93	113	4.45		1130	2541	1362	3061	102,2	6.24	1,05	2.31	✓		
S 750 - 080 - B	S 750 - 080 - C	80	3.15	210	8.27	130	5.12		1142	2568	1381	3104	127,2	7.76	1,18	2.60	✓		
S 750 - 100 - B	S 750 - 100 - C	100	3.94	250	9.84	150	5.91	1152	2589	1396	3138	156,7	9.56	1,33	2.93	✓			
S 750 - 125 - B	S 750 - 125 - C	125	4.92	300	11.81	175	6.89	1159	2607	1408	3166	193,4	11.80	1,52	3.35	✓			

◆ Disposable

