


C102-05

Rotating Eyebolts with Ring

Ordering-Example:

Diferent Lengths On Request.



CODE	MxI1	Working Load Limit W.L.L (t)	d	h	l2	b	c	w	sw	Weight(kg)
C102-05-105-0816	M8x16	0,3	30	105	50	38	13	46	30	0,480
C102-05-105-1018	M10x18	0,3	30	105	50	38	13	46	30	0,480
C102-05-105-1218	M12x18	0,5	30	105	50	38	13	46	30	0,500
C102-05-105-1620	M16x20	1,12	30	105	50	38	13	46	30	0,530
C102-05-105-2030	M20x30	1,12	30	105	50	38	13	46	30	0,530
C102-05-153-2430	M24x30	3,15	40	153	68	58	18	70	48	1,630
C102-05-205-3035	M30x35	8	50	205	95	85	23	95	75	5,300



MxI1	0° Single Leg	0° 2 Legs	90° Single Leg	90° 2 Legs	0° - 45° 2 Legs	45° - 60° 2 Legs	Asymm 2 Legs	0° - 45° 3/4 Legs	45° - 60° 3/4 Legs	Asymm 3/4 Legs	Max. Tightening Couple (Nm)
M8x16	0,6	1,2	0,3	0,6	0,42	0,3	0,3	0,63	0,45	0,3	16
M10x18	0,6	1,2	0,3	0,6	0,42	0,3	0,3	0,63	0,45	0,3	16
M12x18	1	2	0,5	1	0,75	0,5	0,5	1,1	0,75	0,5	28
M16x20	2	4	1,12	2	1,5	1,12	1,12	2,36	1,6	1,12	70
M20x30	2	4	1,12	2	1,5	1,12	1,12	2,36	1,6	1,12	135
M24x30	6,3	12,5	3,15	6,3	4,25	3,15	3,15	6,3	4,75	3,15	230
M30x35	12,5	25	8	16	11,2	8	8	16,8	12	8	465