

Special Sizes Available On Request.



ACCESSORIES & INFORMATIONS

PISTON Ø	WORKING PRESSURES FORCES (N)											
	20 BAR (288 PSI)		50 BAR (720 PSI)		80 BAR (1152 PSI)		100 BAR (1440 PSI)		160 BAR (2300 PSI)		250 BAR (3600 PSI)	
	Pushing	Pulling	Pushing	Pulling	Pushing	Pulling	Pushing	Pulling	Pushing	Pulling	Pushing	Pulling
16	402	245	1005	613	1608	980	2011	1225	3217	1960	5027	3063
25	982	580	2454	1449	3927	2318	4909	2898	7854	4637	12272	7245
32	1608	980	4021	2450	6434	3921	8042	4901	12868	7841	20106	12252
40	2513	1532	6283	3829	10053	6126	12566	7658	20106	12252	31416	19144
50	3927	2318	9817	5796	15708	9274	19635	11592	31416	18548	49087	28981
63	6234	3721	15586	9303	24938	14885	31172	18606	49876	29770	77931	46515
80	10053	6126	25133	15315	40212	24504	50265	30631	80425	49009	125664	76576
100	15708	10053	39270	25133	62832	40212	78540	50265	125664	80425	196350	125664

Special Sizes Available On Request.



BUSHINGS

REFERENCE	PISTON ϕ
ZBS016	16
ZBS025	25
ZBS032	32
	40
ZBS050	50
ZBS063	63
ZBS080	80
ZBS100	100



SCREW SET

REFERENCE	PISTON ϕ
ZSS016	16
ZSS025	25
ZSS032	32
ZSS040	40
ZSS050	50
ZSS063	63
ZSS080	80



COUPLING

REFERENCE	PISTON ϕ
ZTP016	16
ZTP025	25
ZTP032	32
ZTP040	40
ZTP050	50
ZTP063	63
ZTP080	80



PURGE

REFERENCE
ZPG008



O'RINGS SET

For Model A/B	For Model E	For Model F	PISTON ϕ
ZOR016-A			16
ZOR025-A	ZOR025-E	ZOR025-F	25
ZOR032-A	ZOR032-E	ZOR032-F	32
ZOR040-A	ZOR040-E	ZOR040-F	40
ZOR050-A	ZOR050-E	ZOR050-F	50
ZOR063-A	ZOR063-E	ZOR063-F	63
ZOR080-A			80
ZOR100-A			100